

X-Ray Baggage Inspection System

AT8065

Features:

- Multilingual operation
- Automatic built in test and self-diagnosis
- Secure access Key
- Uninterruptable power supply (UPS)
- Threat alert and material classification
- Auto archiving
- Network-Ready
- Energy saving design
- One key turn-off
- Drugs and explosives inspection
- Indication of the date and time
- baggage counter



Technical Specifications:

Tunnel size(mm)	810(L)*655(W)
Conveyor Speed(m/s)	0.2
Conveyor height(mm)	338.5
Conveyor Max Load(kgs)	180
X ray dose per each inspection	Typical 2.5 μ Gy, guarantee 3.0 μ Gy
X ray leakage	Typical .5 μ Gy/h, guarantee 1.0 μ Gy/h
Penetration	Typical 30mm, guarantee 27mm
Wire Resolution	Typical AWG36, guarantee AWG34
Penetration Resolution	Typical AWG32, guarantee AWG30
Spatial resolution	Typical dia1.3mm, Vertical: dia1.3mm; Guarantee dia1.6mm Vertical: dia1.6mm
Power Consumption	Max 1KVA
Noise	< 60 dB
Film Safety	Guarantee ASA/ISO1600 Film
Image System	
X-ray Sensor	L-Shaped Photodiode Array (multi-energetic), 16bit Deep
Image Display	High resolution of 1024 * 1280-pixel, Image Grey Level: 65536
Image Enhancement	1-64times enlargement continuity, Color/BW, negative, high/low penetration, organic /inorganic Stripping, general enhancement, and pseudo color, etc.
Image Recall	All preceding images recallable, retrieval
Explosives & Narcotics Detection	Explosives & narcotics alarm and highlight according to atomic number signature
High Density Region Alarm	impenetrable region alarm and highlight, for possible concealing of threats and contrabands
Threat Image Projection	Inserting fictional, but realistic images of threat items into baggage during screening operation, for maintenance of vigilance, as well as training and assessment of image identification capability
Image Archive	Up to 200,000 images stored automatically, enable transferring to USB disk, and converting to JPG, BMP and other general formats

TECHNIC TRAINERS PRIVATE LIMITED

Regd Office: House No11, Upper Ground Floor, New Gupta Colony Priyadarshini Vihar, Phase-1 Delhi-110009

Mob: +919818288089, +917982271248

sales@tekoworld.com | tekosales2@gmail.com | www.tekoworld.com

CIN: U80904DL2017PTC326736

Branch Office : Delhi | Noida | Mumbai | Kolkata | Lucknow | Coimbatore | Ludhiana | Chandigarh | Panipat | Jaipur | HP | Nagpur | Jammu



Miscellaneous Functions	Time/date display, counters, user management, system-on/X-ray-on timers, power on self test, built-in diagnostic facilities, dual-direction scanning, system log, system standby and stimulant training, ADS etc.
Network Applications	Multiple remote applications available based on Ethernet LAN and windows platform, such as image centralized storage and identify, recheck workstation, and network TIP, etc (Optional).
Images process	24bit real time processing ,4colors analysis, Images displayed marked date and ID NO, Count the number of bags
X-ray Generator (single)	
Anode Voltage	140 KV
Anode Current	0.7mA
Generate angle	82 degree upward
Generate direct	from top to bott0m
Cooling / Duty Cycle	Oil Cooling /100%
Computer and other	
Monitor	High Resolution Color, LCD Accord, 17inch
Hard Disk	SEAGATE 500G 3.5"
CPU	G1610 2.6G
Storage	2GB 1600MHz DDR3 Innodisk
Main board	H61 SYM76993VGGA
Physical Specifications	
Unit weight (kgs)	640
Unit size (mm)	2848.5(L)*1095(W)*1535.5(H)
Gross weight (kgs)	800
Packing size	1. 213*121*179cm 2. 115*90*142cm
Operating Environment	
Operation temperature/Humidity	0°C-45°C / 5%-95%(non-condensing)
Storage Temperature/Humidity	-40°Cto 70°C / 5%-95%(non-condensing)
Operation Power	220VAC (±10%) 50±3Hz (Optional: 100VAC,110VAC,120VAC,200VAC)
UPS	15mins, 30mins, 60mins etc, optional